

Locinox - Standard Gate Lock with Exit Push Pad

This variation of the Locinox Standard lock is suitable for gates that are part of an emergency exit route and a panic situation is unlikely to arise - and for ease of operation when carrying parcels or other items requiring both hands.

Exit and entry using the push pad or handle is only possible when the deadbolt is not engaged. The deadbolt is engaged by making one turn of the key. The deadbolt will then provide additional night-time security. With the deadbolt engaged, exit and entry are NOT possible using the handle or push pad.

The Locinox Standard lock with push pad is easy to install and requires no welding of any parts. Its aluminium lock case and stainless steel lock parts ensure a rust free life - not rusting from the inside or outside.

A strong tamper resistant construction provides superior levels of security and decreases the likelihood of damage to the lock. All fixing screws are only accessible when the gate is open, discouraging theft of the lock. Both latch bolt and deadbolt projection are adjustable without removing the lock case making final adjustment really easy.

It is available in three colours, black, silver and green. Three models are offered to fit gate frame profiles: 10-20 mm solid bar, 30-50 mm box section and 40-60 mm box section (see ordering details).

Each lock comes with a handle, push pad, keep, locking cylinder with three keys and a blank cylinder. We also provide a drawing giving drilling hole sizes and positions.

Technical Overview

Latch rotates 180° for left and right handing

15 mm latch bolt retraction

25 mm deadbolt throw with 1 turn of key

20 mm latch bolt adjustment

20 mm deadbolt adjustment

Deadbolt inoperative with blank cylinder

Deadbolt operative with keyed cylinder

Stainless steel chassis and lock parts

Models for 10 mm solid up to 60 mm box section



Ordering Details

Black lock with silver push pad

GATELOCK015 - for 10-20 mm solid profiles

GATELOCK014 - for 30-50 mm box section

GATELOCK023 - for 40-60 mm box section

Silver lock with silver push pad

GATELOCK017 - for 10-20 mm solid profiles

GATELOCK016 - for 30-50 mm box section

GATELOCK024 - for 40-60 mm box section

Standard Gate Lock with Push Pad - Dimensions and Fitting Detail

